Data sheet 27140.9 PQI 2,5/10 RD





Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 49.9 mm, Colour: Red

Business data

Article number	<u>27140.9</u>
Article name	PQI 2,5/10 RD
GTIN (EAN)	4044211225261
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	8.5 g
Weight per piece (including packaging)	8.73 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	27140.9
Product description	Insulated cross-connector

Data sheet





Technical data		
Dimensions		
Length	4 mm	
Width	49.9 mm	
Height	19.4 mm	
Pitch size	5.1 mm	
Ratings		
Max. voltage	800 V	
Rated current	24 A	
Current load, max.	24 A	
Rated cross-section	2.5 mm ²	
Contamination degree	3	
Connection data		
No. of poles	10	
Materials		
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-0	
Working temperature, min.	-40 °C	
Working temperature, max.	120 °C	
Further technical data		
Mounting type	Plug in	
Insulation available	✓	
Touch protection is available	✓	
Number of bridged terminals	10	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2022-06-10	
REACH Candidate Substance Note	No	
RoHS Conform	yes	

Data sheet 27140.9 PQI 2,5/10 RD



Media

Data sheet

27140.9 PQI 2,5/10 RD



Accessories

##INVERSE##CONTA-CONNECT



Three-level initiator terminal |Multi-wire terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27046.6	PVMAK 2,5 GR	4044211227289	50 ST



Three-level initiator terminal |Multi-wire terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27047.6	PVMAK 2,5/SV GR	4044211227296	50 ST



Three-level initiator terminal |Multi-wire terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27048.6	PIKD 2,5/1PE/L/L GR	4044211227173	50 ST



Protective-earth double-level terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27037.2	PSLD 2,5 GNYE	4044211226718	50 ST



Three-level initiator terminal | Multi-wire terminal, Push-in-connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5,1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27040.2	PIKD 2,5/SV/PE GNYE	4044211227227	50 ST



Three-level initiator terminal |Multi-wire terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27042.6	PIKD 2,5/PE/L/L GR	4044211227258	50 ST



##INVERSE##CONTA-CONNECT



Three-level initiator terminal |Multi-wire terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27043.6	PIKD 2,5/PE/L/N GR	4044211227265	50 ST



Three-level initiator terminal |Multi-wire terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27045.6	PIKD 2,5/L/L/N GR	4044211227272	50 ST



Three-level initiator terminal |Multi-wire terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27049.6	PIKD 2,5/1PE/L/N GR	4044211227180	50 ST



Three-level initiator terminal |Multi-wire terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27050.6	PIKD 2,5/1/L/L GR	4044211227302	50 ST



Double-level terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27051.6	PRKD 2,5/PE/L GR	4044211227159	50 ST



Double-level terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27036.6	PRKD 2,5 GR	4044211226695	50



Double-level terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27052.6	PRKD 2,5/PE/N GR	4044211227166	50 ST

Data sheet

27140.9 PQI 2,5/10 RD



##INVERSE##CONTA-CONNECT



Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27009.2	PSL 2,5/3A GNYE	4044211223847	50 ST



Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27007.2	PSL 2,5/2A GNYE	4044211223809	50 ST



Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27011.2	PSL 2,5/4A GNYE	4044211223885	50 ST



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27008.6	PRK 2,5/3A GR	4044211223830	50